









SEZIONE A-A
SCALA 1 : 1



Stroke per Jaw: 4 mm
Closing Force at 6 bar: 110+110 N
Opening Force at 6 bar: 120+120 N
Repeat accuracy: ± 0.01 mm
Fluid consumption double stroke: 4 cm³

 EFFECTO®		Via Roma 141-143 28017 San Maurizio d'Opaglio (NO) Tel. +39 032296142 Via Don Primo Mazzolari 4 26012 Castelleone (CR): Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS.WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE. FIRST ANGLE PROJECTION 		Eng:- -		Commercial Description:	
		PROD:- -		HPG-205-P-4-U-SM-8-P-B-S	
		QC out:- -		Description:	
		Sales:- -		Gripper HPG 205	
General Tolerances in accordance with ISO 2768-m H CENTERING HOLE: ISO 6411		Part Number:		A3	
		HP205NCL			
DATA: 27/03/2026		Weight: 0.18Kg		Sheet: 1 of 2	
				Rev:00	