




Stroke per Jaw: 8 mm
Closing Force: 350+350 N
Opening Force: 210+210 N
Repeat accuracy: ± 0.01 mm
Nominal Operating Pressure: 6 bar
Max Operating Pressure: 8 bar
Fluid consumption double stroke: 42 cm3

 EFFECTO		Via Roma 141-143 28017 San Maurizio d'Opaglio (NO) Tel. +39 032296142 Via Don Primo Mazzolari 4 26012 Castelleone (CR) Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
THE INFORMATION CONTAINED HEREIN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS. WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.		Eng: 23/04/2026		Commercial Description:	
		PROD: M. Tozzini 23/04/2026		HPG-208-P-8-U-CM-8-P-B-S	
		QC out:		Description:	
		Sales: -		Gripper HPG 208 CM	
		General Tolerances in accordance with ISO 2768-m H CENTERING HOLE: ISO 6411		Part Number:	
		DATA: 08/05/2026		HP208NCM	
		Weight: 0.68Kg		Sheet: 2 of 2	
				Rev:00	
				A3	