







Stroke per Jaw: 8 mm
Closing Force: 1380+1380 N
Opening Force: 2820+2820 N
Repeat accuracy: ± 0.015 mm
Nominal Operating Pressure: 6 bar
Max Operating Pressure: 8 bar
Fluid consumption double stroke: 338 cm³

 EFFECTO [®]		Via Roma 141-143 28017 San Maurizio d'Opaglio (NO) Tel. +39 032296142 Via Don Primo Mazzolari 4 26012 Castelleone (CR) Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
		Commercial Description: HPG-216-P-8-U-AM-8-P-B-S		Description: Gripper HPG216 SMA	
THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS. WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.		Eng: 23/04/2026 PROD: M. Tozzini 24/04/2026 QC out: - - Sales: - -		Part Number: HP216SMA	
		General Tolerances in accordance with ISO 2768-m H CENTERING HOLE: ISO 6411 DATA: 08/05/2026		Weight: 3.88Kg Sheet: 2 of 2 Rev:00	
FIRST ANGLE PROJECTION 				A3	