




Stroke per Jaw: 10 mm
Closing Force: 820+820 +820 N
Opening Force: 480+480+480 N
Repeat accuracy: ± 0.01 mm
Nominal Operating Pressure: 6 bar
Max Operating Pressure: 8 bar
Fluid consumption double stroke: 190 cm³

M5 pressurization

 EFFECTO THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS. WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.		Via Roma 141-143 28017 San Maurizio d'Opaglio (NO) Tel. +39 032296142 Via Don Primo Mazzolari 4 26012 Castelleone (CR) Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
		Commercial Description: HPG-311-P-10-U-CM-8-P-B-S		Description: Gripper HPG 311 CM	
 FIRST ANGLE PROJECTION		Eng: 28/04/2026 PROD: M. Tozzini 29/04/2026 QC out: - Sales: -		Part Number: HP311NCM	
		General Tolerances in accordance with ISO 2768-m H CENTERING HOLE: ISO 6411 DATA: 08/05/2026		Weight: 1.94Kg	Sheet: 1 of 2 Rev:00