





Stroke per Jaw: 15 mm
Closing Force: 528+528 N
Opening Force: 632+632 N
Repeat accuracy: $\pm$ 0.01 mm
Nominal Operating Pressure: 6 bar
Max Operating Pressure: 12 bar
Fluid consumption double stroke: 106 cm3

 THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS. WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.		Via Roma 141-143 28017 San Maurizio d'Opaglio (NO) Tel. +39 032296142 Via Don Primo Mazzolari 4 28012 Castellone (CR) Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
		Eng:		Commercial Description:	
		PROD:		MOP-90-P-15-U-SM-12-N-B-N	
		QC out:		Description:	
		Sales: -		MOP90 Gripper	
		General Tolerances in accordance with ISO 2768-m H		Part Number:	
		CENTERING HOLE: ISO 6411		500.101.000.00	
		DATA: 05/05/2026		Weight: Kg	
				Sheet: 1 of 1	
				Rev:01	
				A2	