




Stroke per Jaw: 8 mm
Closing Force: 325+325 N
Opening Force: 260+260 N
Repeat accuracy: ± 0.01 mm
Nominal Operating Pressure: 6 bar
Max Operating Pressure: 12 bar
Fluid consumption double stroke: 28 cm³

		Via Roma 141-143 28017 San Maurizio d'Ossiglio (NO) Tel. +39 03296142 Via Don Primo Mazzolari 4 28012 Castellone (CR) Tel. +39 037435138 www.effectogroup.com		OUTLINE DO NOT SCALE THE DRAWING	
		Commercial Description: QPG-TECH-208-P-8-U-SM-12-P-B-S Description: QPG-tech208 Gripper Part Number: QT080NBA		A2	
THE INFORMATION CONTAINED HERE IN IS THE SOLE PROPERTY OF EFFECTO GROUP S.P.A. THE DIMENSIONS ARE INDICATIVE AND SUSCEPTIBLE TO CHANGE DUE TO TECHNICAL IMPROVEMENTS. WE RESERVE THE RIGHT TO MAKE CHANGES WITHOUT NOTICE.		Eng: 06/05/2026 PROD: M. Tozzini 07/05/2026 QC out: - Sales: -		General Tolerances in accordance with ISO 2768-m H CENTERING HOLE: ISO 6411 DATA: 07/05/2026	
		FIRST ANGLE PROJECTION 		Weight: 0.65Kg Sheet: 1 of 1 Rev: 00	