


Facing heads

TRD - Double slide

TRD is a double slide facing head with rigid design for low spindle needs.

Advantages



- Large tool mounting surfaces.
- Minimum backlash.
- Low coefficient of friction.
- Adaptor plate (for DIN2079 spindle) upon request.
- Driven mechanically, with hydraulically or NC electromechanical cylinder, through drawbar (not supplied parts).



SPECIFICATIONS

Model	Diameter	Slide Stroke	Hub Stroke	Rack Angle	Stroke Ratio (approx.)	Weight
TRD100-K1	100 mm	17 mm	20.3 mm	40°	1.2:1	3.3 Kg
	3.94 in	0.67 in	0.80 in			7.28 lb
TRD100-K2	100 mm	10 mm	19.7 mm	27°	2:1	3.3 Kg
	3.94 in	0.39 in	0.78 in			7.28 lb
TRD125-K1	125 mm	22 mm	26.2 mm	40°	1.2:1	4.6 Kg
	4.92 in	0.87 in	1.03 in			10.14 lb
TRD125-K2	125 mm	13 mm	25.6 mm	27°	2:1	4.6 Kg
	4.92 in	0.51 in	1.01 in			10.14 lb
TRD160-K1	160 mm	30 mm	35.8 mm	40°	1.2:1	11.7 Kg
	6.30 in	1.18 in	1.41 in			25.79 lb
TRD160-K2	160 mm	18 mm	35.4 mm	27°	2:1	11.7 Kg
	6.30 in	0.71 in	1.39 in			25.79 lb

Working Temperature **5 - 60 °C (41 - 140 °F)**




	G	aa
TRD100-K1	20.3	17
TRD100-K2	19.7	10
TRD125-K1	26.2	22
TRD125-K2	25.6	13
TRD160-K1	35.7	30
TRD160-K2	35.4	18

PRODUCT INFORMATION

TRD - Double slide



02.25_Rev.5



Options

TRD-K2: Rack angle 27° (on request)

	A	B	C	D	E	F	G	H	I	J (left)	K	L	M	N	O	P	Q	R	S	T
TRD100-K1	100 (3.94)	110.3 (4.34)	50 (1.97)	30 (1.18)	49 (1.93)	4 (0.16)	20.3 (0.80)	8 (0.31)	14 (0.55)	M10X1	12 (0.47)	16 (0.63)	20 (0.79)	8 (0.31)	25 (0.98)	65 (2.56)	10.3 (0.41)	42 (1.65)	84 (3.31)	M8
TRD100-K2	100 (3.94)	110.3 (4.34)	50 (1.97)	30 (1.18)	49 (1.93)	4 (0.16)	19.7 (0.78)	8 (0.31)	14 (0.55)	M10X1	12 (0.47)	16 (0.63)	20 (0.79)	8 (0.31)	25 (0.98)	65 (2.56)	10.3 (0.41)	42 (1.65)	84 (3.31)	M8
TRD125-K1	125 (4.92)	131.2 (5.17)	58 (2.28)	37 (1.46)	57 (2.24)	4 (0.16)	26.2 (1.03)	8 (0.31)	16 (0.63)	M12X1.5	14 (0.55)	20 (0.79)	26 (1.02)	8 (0.31)	30 (1.18)	90 (3.54)	14.6 (0.57)	54 (2.13)	110 (4.33)	M8
TRD125-K2	125 (4.92)	131.2 (5.17)	58 (2.28)	37 (1.46)	57 (2.24)	4 (0.16)	25.6 (1.01)	8 (0.31)	16 (0.63)	M12X1.5	14 (0.55)	20 (0.79)	26 (1.02)	8 (0.31)	30 (1.18)	90 (3.54)	14.6 (0.57)	54 (2.13)	110 (4.33)	M8
TRD160-K1	160 (6.30)	165.7 (6.52)	70 (2.76)	50 (1.97)	69 (2.72)	5 (0.20)	35.7 (1.41)	10 (0.39)	25 (0.98)	M16X1.5	18 (0.71)	25 (0.98)	30 (1.18)	8 (0.31)	35 (1.38)	110 (4.33)	14.6 (0.57)	70 (2.76)	140 (5.51)	M10
TRD160-K2	160 (6.30)	165.7 (6.52)	70 (2.76)	50 (1.97)	69 (2.72)	5 (0.20)	35.4 (1.39)	10 (0.39)	25 (0.98)	M16X1.5	18 (0.71)	25 (0.98)	30 (1.18)	8 (0.31)	35 (1.38)	110 (4.33)	14.6 (0.57)	70 (2.76)	140 (5.51)	M10

	U	V	W	X	Y	Z	aa	bb	cc	dd	ee	ff	Spindle size	No. of slide holes	Spindle mounting holes spacing
TRD100-K1	M8	12 (0.47)	10 (0.39)	36 (1.42)	8 (0.31)	8.5 (0.33)	17 (0.67)	10 (0.39)	5 (0.20)	56 (2.20)	12 (0.47)	3 (0.12)	30 (1.18)	6	4x90° - 3x120°
TRD100-K2	M8	12 (0.47)	10 (0.39)	36 (1.42)	8 (0.31)	5 (0.20)	10 (0.39)	10 (0.39)	5 (0.20)	56 (2.20)	12 (0.47)	3 (0.12)	30 (1.18)	6	4x90° - 3x120°
TRD125-K1	M8	12 (0.47)	12 (0.47)	46 (1.81)	8 (0.31)	11 (0.43)	22 (0.87)	10 (0.39)	6 (0.24)	72 (2.83)	12 (0.47)	3 (0.12)	40 (1.57)	6	6x60°
TRD125-K2	M8	12 (0.47)	12 (0.47)	46 (1.81)	8 (0.31)	6.5 (0.26)	13 (0.51)	10 (0.39)	6 (0.24)	72 (2.83)	12 (0.47)	3 (0.12)	40 (1.57)	6	6x60°
TRD160-K1	M10	16 (0.63)	13 (0.51)	56 (2.20)	10 (0.39)	15 (0.59)	30 (1.18)	12 (0.47)	6 (0.24)	86 (3.39)	15 (0.59)	3 (0.12)	40 (1.57)	6	4x90°
TRD160-K2	M10	16 (0.63)	13 (0.51)	56 (2.20)	10 (0.39)	9 (0.35)	18 (0.71)	12 (0.47)	6 (0.24)	86 (3.39)	15 (0.59)	3 (0.12)	40 (1.57)	6	4x90°

* Dimensions are in millimeters (inches).

** All dimensions are descriptive and subject to variation for technical upgrading. We reserve the right to make variations without prior notification



Effecto Group S.p.A.
Via Roma, 141/143
28017 San Maurizio d'Opaglio (NO) - IT
Tel. +39 0322 96142
info@effecto.com

Effecto, Inc.
648 Saratoga Road
Glenville, NY 12302 - US
Tel. +1 518 384 1000
info@us.effecto.com

www.effecto.com

Effecto GmbH
Liegnitzer Str. 6
82194 Gröbenzell - DE
Tel. +49 8142 59397 0
info@de.effecto.com